

## 

(43) International Publication Date 18 January 2001 (18.01.2001)

PCT

## (10) International Publication Number

(51) International Patent Classification?: B65G

WO 01/04025 A2

(21) International Application Number: PCT/US00/19090

Dam, WI 53916 (US). VANDERHOEVEN, Dennis, A. [-/US]; W8718 Birdie Lane, Beaver Dam, WI 53916 (US). BUSSE, Brian, E. [--/US]; 125 Talmadge Street, Madison, WI 53704 (US).

(22) International Filing Date:

13 July 2000 (13.07.2000) English

(74) Agents: KELLEY, Timothy, M. et al.; Michael Best & Friedrich LLP. 100 East Wisconsin Avenue, Milwaukee, WI 53202-4108 (US).

(25) Filing Language: (26) Publication Language:

English

(81) Designated States (national): BR, CA, MX, US.

(30) Priority Data: 60/143.575 60/149.002

13 July 1999 (13.07.1999) 13 August 1999 (13.08.1999) (84) Designated States (regional): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC. NL, PT, SE).

(71) Applicant (for all designated States except US): ARROW-HEAD SYSTEM LLC [US/US]; 124 North Columbus Street, P.O. Box B. Randolph, WI 53956 (US).

Published:


Without international search report and to be republished upon receipt of that report.

(72) Inventors; and

(75) Inventors/Applicants (for US only): VAN NICE, Jeff, G. [US/US]; 212 Scipple Boulevard, Apartment #05, Beaver ning of each regular issue of the PCT Gazette.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the begin-

(54) Title: SEPARATOR SHEET HANDLING ASSEMBLY



(57) Abstract: The present invention is embodied in a separator sheet handling assembly (10) that includes a lifting assembly (20) adapted to receive a pallet (12) containing a stack of separator sheets (14). The lifting assembly (20) positions the stack of separator sheets (14) into a predetermined location where a feed assembly (30) engages a separator sheet (16) positioned at the top of the stack of separator sheets (14). The feed assembly (30) removes the separator sheet (16) and transports it to a test assembly (50) where the separator sheet (16) is monitored for a particular characteristic such as cleanliness or structural integrity. The separator sheet (16) is delivered to a first storage assembly (60) if the separator sheet (16) has the particular characteristic, or a second storage assembly (70) if the separator sheet (16) does not include the particular characteristic.